



Material Safety Data Sheet

300 Series Stainless Steel	
Common Name	
Tool Wrap	20
Identity (Trade Name As Used On Label) and Product Code	

Manufacturer Precision Brand Products Inc.	Phone Number (For Information) 630-969-7200
Address 2250 Curtiss Street Downers Grove IL 60515 USA	Emergency Phone Number Chemtrec 800-424-9300 USA & Canada 202-483-7616 International
Date Prepared 02 Dec 99	Date Reviewed 14 Jan 02

SECTION 1 -- MATERIAL IDENTIFICATION AND INFORMATION			
COMPONENTS--Chemical Name & Common Names	%	OSHA PEL (mg/m ³)	ACGIH TLV (mg/m ³)
Iron (Fe) CAS No. 7439-89-6	52-78	10, iron oxide form, fume	5, iron oxide form, dust and fume
Chromium (Cr) CAS No. 7440-47-3	12-24	1, metal & insoluble salts 0.5, Cr (III) compounds 0.1, Cr (VI) compounds	0.5, metal & Cr(III) compounds 0.05, Cr(VI) water soluble compounds 0.01, Cr(VI) water insoluble compounds
Nickel (Ni) CAS No. 7440-02-0	6.0-19	1, metal & insoluble compounds	1.5 metal 0.1, soluble compounds 0.2 insoluble compounds
Molybdenum (Mo) CAS No. 7439-98-7	0-5.0	5, Soluble Mo compounds (as Mo) 15, Insoluble Mo compounds, total dust (as Mo)	5, soluble Mo compounds (as Mo) 10, Insoluble Mo compounds (as Mo)
Silicon (Si) CAS No. 7440-21-3	0-6.0	15, total dust 5, respirable fraction	10, total dust
Manganese (Mn) CAS No. 7439-96-5	0-2.0	5 Ceiling, Mn compounds and Mn fume (as Mn)	0.2, elemental and inorganic compounds (as Mn)
Tungsten (W) CAS No. 7440-33-7	0-1.8	15, total dust (PNOR) 5, respirable fraction (PNOR) (not regulated)	1 mg/m ³ , 3 mg/m ³ STEL soluble W compounds (as W) 5 mg/m ³ , 10 mg/m ³ STEL insoluble W compounds (as W)
Aluminum (Al) CAS No. 7429-90-5	0-1.5	15, metal, total dust (as Al) 5, metal, respirable fraction (as Al)	10, metal dust 5, welding fume
Columbium (Cb) CAS No. 7440-03-1	0-1.0	15, total dust (PNOR) 5, respirable fraction (PNOR) (not regulated)	10, total dust (PNO) (not classified)
Titanium (Ti) CAS No. 7440-32-6	0-0.7	15, Titanium Dioxide form, total dust	10, Titanium Dioxide form, total dust
Copper (Cu) CAS No. 7440-50-8	0-.75	0.1, fume (as Cu); 1 dust and mist (as Cu)	0.2, fume (as Cu); 1, dusts and mists (as Cu)
Cobalt (Co) CAS No. 7440-48-4	0-1.0	0.1, metal, dust and fume (as Co)	0.02, elemental and inorganic compounds (as CO)

Notes: 1) All exposure limits are 8-hour TWAs unless otherwise specified. 2) As defined by OSHA, STEL (Short Term Exposure Limit) is an employee's fifteen-minute, time-weighted average exposure which must not be exceeded during a workday. 3) All commercial metals may contain small amounts of various elements in addition to those specified. These small quantities (less than 0.1%), frequently referred to as "trace" or "residual" elements, generally originate in the raw material used. These elements may include, but are not limited to the following: Sulfur, Phosphorous, Nitrogen, Aluminum, Arsenic, Boron, Cadmium, Calcium, Lead, Tin, Titanium, Vanadium, and Zirconium. Abbreviations and acronyms are defined in Section 12.

SECTION 2 -- PHYSICAL / CHEMICAL CHARACTERISTICS			
Boiling Point	NIF for steel products (Fe-5432/ Cr-3992/Ni-5252 °F)	Specific Gravity (H ₂ O = 1)	7 - 9
Vapor Pressure (mm Hg @ 68 °F)	Negligible	Melting Point	NIF for steel products. (Fe:2797/Cr-3452/Ni-2651 °F)
Vapor Density (Air = 1)	N/A	Evaporation Rate	N/A
Solubility in Water	Insoluble	pH	N/A
Appearance and Odor	Silver-gray metallic solid form, odorless		

SECTION 3 -- FIRE AND EXPLOSION HAZARD DATA					
Flash Point and Method Used N/A	Auto-Ignition Temperature N/A	General Fire Hazard: None for solid formed product	Flammability Limits	LEL N/A	UEL N/A
Extinguisher Method	For solid formed product, as appropriate for surrounding fire. A fire involving finely divided particles should be treated as a Class D combustible metal fire. Fire should be extinguished by a properly trained and experienced firefighter. Proper care should be taken in applying extinguishing agent and in allowing to burn itself out.				
Fire Fighting Equipment	For solid formed product, as appropriate for surrounding fire. Positive pressure SCBA and structural firefighter's protective clothing should be used at a minimum for surrounding fire.				
Unusual Fire or Explosion Hazards	<p>This solid formed product does not constitute a fire or explosion hazard. Finely divided, suspended particulate may present a fire and explosion hazard in the presence of an ignition source. In addition, applied coatings may be combustible. For fires involving coated product, consult the appropriate coating MSDS.</p> <p>Finely divided product (e.g. dust, shavings, etc.) may be combustible. May be ignited by heat, sparks, or flames. May burn rapidly with flare-burning effect. Fire may produce irritating or poisonous gases. High concentrations of airborne dust in an enclosed area can explode or burn if exposed to a source of ignition. Care should be taken to avoid the generation of airborne dust. Use of water on finely divided product may cause explosive hydrogen gas and heat to be evolved.</p>				
Explosion Data	<u>Sensitivity/Mechanical Impact:</u> N/A for solid product. <u>Sensitivity/Static Discharge:</u> N/A for solid product.				
Hazardous Combustion Products	N/A for solid formed product. Toxic metal and metallic oxide fumes may be evolved from fires involving finely divided particles and during torch-cutting operations.				

SECTION 4 – STABILITY AND REACTIVITY		
STABILITY <input checked="" type="checkbox"/> Stable (Under normal conditions of use, storage and transport for solid formed product.) <input type="checkbox"/> Unstable	Conditions To Avoid	Contact with incompatible materials. Avoid creating finely divided concentrated airborne particulate in the presence of ignition sources.
Incompatible Materials	Oxidizers. Reacts with strong acids to form explosive hydrogen gas and heat.	
Hazardous Decomposition Products	Extreme heat from fire or processing (e.g. welding, brazing, machining, etc.) may produce toxic or irritating airborne particulate, including metal and metallic oxide fumes. Reaction of some metals with water, steam, acids, etc. can evolve hydrogen, which is a highly dangerous fire and explosion hazard.	
Hazardous Polymerization	<input type="checkbox"/> May Occur <input checked="" type="checkbox"/> Will Not Occur	

SECTION 5 -- HEALTH HAZARD DATA
GENERAL HAZARD STATEMENT: Solid metallic products distributed by Precision Brand Products are generally classified as "articles" and do not constitute a hazardous material in solid form under the terms of the OSHA Hazard Communication Standard. Any articles manufactured from these solid products would be generally classified as non-hazardous. <u>However</u> , some metallic elements contained in these products have been determined to be toxic and are subject to regulatory controls. These elements can be emitted as airborne contaminants under certain processing conditions such as burning, melting, cutting, sawing, brazing, grinding, milling, and machining. Certain materials and equipment utilized in processing of steel products (cutting/machining fluids, coatings, processing lubricants, cleaning/pickling chemicals, welding fluxes, torch and plasma cutting systems) may constitute a health hazards and should be treated accordingly.

SECTION 5 -- HEALTH HAZARD DATA- Continued	
EMERGENCY OVERVIEW: Odorless solid product in various forms, silver-gray color. This formed solid metal product poses little or no immediate health or fire hazards. Product may be coated – refer to appropriate coating MSDS for physical and health hazards. When product is subjected to welding, burning, melting, sawing, brazing, grinding, or other similar processes, potentially hazardous airborne particulate and fumes may be generated. These operations should be performed in well-ventilated areas, and if appropriate, respiratory protection and other PPE should be utilized.	
PRIMARY ROUTES OF ENTRY <input checked="" type="checkbox"/> Inhalation ¹ <input type="checkbox"/> Ingestion <input type="checkbox"/> Skin Absorption <input type="checkbox"/> Not Hazardous <small>(¹ Of dust or fume during welding, burning, melting, cutting, brazing, grinding, machining, and other operations.) NOTE: The composition of fumes from welding are dependent not only on the metal being welded, but also on the welding process and electrodes used. A full health assessment should be performed by a competent health and safety professional for all welding and other operations performed on this product.)</small>	CARCINOGENICITY The carcinogenicity of this solid product as a whole has not been tested. Individual components and some compounds of these elemental metals may have been associated with carcinogenicity by NTP and IARC. No component greater than 0.1% by weight within this solid product is regulated by OSHA within 29 CFR 1910 Subpart Z as a carcinogen.
HEALTH HAZARDS	<p>Acute Inhalation: Exposures to high concentrations of metallic fumes or dusts may result in irritation of the respiratory tract and/or sensitization of the lungs and other mucous membranes. Excessive inhalation of fumes from many metals can produce an acute reaction known as “metal fume fever” (symptoms shown below under “Signs and Symptoms of Exposure”). Eyes: Exposure to high concentrations of fumes or dusts may cause irritation and/or sensitization. Skin: Exposure to dust may cause irritation or sensitization, possibly leading to dermatitis. Ingestion: Ingestion of harmful amounts of product as distributed is unlikely due to its solid, insoluble form. Ingestion of dust may cause nausea and/or vomiting. Serious effects may occur if large amounts of dust are swallowed.</p> <p>Chronic EXCESSIVE AND REPEATED EXPOSURES TO FUME OR DUST GENERATED DURING PROCESSING MAY CAUSE: Allergic sensitization – dermatitis and asthma. * Lung inflammation and damage – pneumonitis, pneumonia, bronchitis, siderosis (benign lung disease caused by inhaling iron particles) diffuse pulmonary fibrosis. * Nasal perforation and nasal cavity damage. * Eye inflammation. * Central nervous system damage, possibly permanent. * Kidney damage. * Liver damage. * Gout – inflammation of the joints (associated with some metals.)</p>
Signs and Symptoms of Exposure	*Redness, swelling, itching and/or irritation of the skin and eyes. * Respiratory difficulties – coughing, wheezing, shortness of breath, dyspnea, decreased pulmonary function. * Metal fume fever – symptoms consist of chills and fever (very similar and easily confused with flu symptoms), a metallic taste in the mouth, dryness and irritation of the throat. The symptoms occur a few hours after excessive exposures and usually last 12 to 48 hours. Long term effects from metal fume fever have not been noted in the literature. * Central nervous system effects may show languor, sleepiness, weakness, emotional disturbances, spastic gait, paralysis. * Kidney damage may be seen as changes in urine output and appearance, lower back pain, and edema (swelling from fluid retention). * Liver damage may be seen as loss of appetite, jaundice (yellowish skin color), and occasional pain in the upper abdomen on the left side. * Anorexia and weight loss. NOTE: For specific toxicological and other chronic effect information concerning the components of this solid steel product, refer to SECTION 8, Toxicological Information.
Medical Conditions Generally Aggravated by Exposure	For airborne fume and dust, preexisting diseases of the lungs, skin, eyes, and other mucous membranes. Inhalation of high concentrations of Iron Oxide may possibly enhance the risk of lung cancer development in workers exposed to pulmonary carcinogens.
Synergistic Materials	Inhalation of high concentrations of Iron Oxide may possibly enhance the risk of lung cancer development in workers exposed to pulmonary carcinogens.
EMERGENCY FIRST AID PROCEDURES	
Eye Contact	Immediately flush with large amounts of running water for several minutes. Seek prompt medical attention.
Skin Contact	If dust gets on skin, wash contaminated area with soap and water. Remove and wash contaminated clothing. If a persistent rash or irritation occurs, seek medical attention.
Inhalation	If overexposure occurs, immediately remove victim from the adverse environment to fresh air and seek medical attention. If breathing has stopped, certified individuals should perform CPR. Keep affected person warm and at rest.
Ingestion	Get medical attention immediately.

SECTION 6 – EXPOSURE CONTROLS/PERSONAL PROTECTION			
Respiratory Protection	When engineering or administrative controls cannot maintain exposures below permissible limits during welding, brazing, machining, and other processes which may generate airborne contaminants or while being instituted, use an approved respirator. If respiratory protection is required, all appropriate requirements as set forth in 29 CFR 1910.134 must be met. A competent health and safety professional should be consulted for respirator selection, fit testing, and training. Use an approved positive-pressure, air-supplied respirator if exposure levels are unknown or any other circumstance where an air-purifying respirator would not be adequate.		
Protective Gloves	Suitable for protection against physical injury and skin contact during handling and processing.	Eye Protection	Safety glasses or goggles when there is a reasonable probability of flying particles or high levels of airborne dust or fume.
Engineering Controls	Local and/or general exhaust ventilation should be used to keep worker exposure below applicable exposure limits (See Section 1) during welding, brazing, grinding, machining, and other processes, which may generate airborne contaminants.		
Other Protective Clothing and Equipment	Adequate footwear (safety shoes if necessary) and clothing that protects skin from prolonged or repeated contact. Change clothing if there is a reasonable probability of contamination.		

SECTION 7-- PRECAUTIONS FOR SAFE HANDLING & USE/LEAK PROCEDURES	
Steps to be Taken In Case Material Is Released	<p>Minimal problems with spills of this product would occur because of its solid form. The following precautions apply to spills involving finely divided particles:</p> <ul style="list-style-type: none"> • Shut off ignition sources; no flares, smoking or flames should be in or near hazard area. • Do not touch or walk through spilled material. Clean up using methods which avoid dust generation. • Compressed air should not be used to clean up spills. • During cleanup, skin and eye contact and inhalation of dust should be avoided as much as possible. • Provide local exhaust or dilution ventilation as required. • Appropriate PPE should be worn during cleanup if exposure limits are exceeded. (See Section 6, Control & Protective Measures.) • Collect material in compatible and appropriately labeled containers. • For small dry spills, place material into clean dry container with a clean shovel and cover loosely. Move container from spill area. • Comply with federal, state/provincial and local regulations regarding reporting of spills and waste disposal.
Disposal Considerations	If product as shipped becomes a solid waste, it would not be classified as a hazardous waste, and it should be recycled. Product dusts from processing may be classified as a hazardous waste, depending on various properties of the dust (e.g. toxicity, solubility, flammability), which are defined further within 40 CFR 261, possibly more restricting state and/or local regulations. Solid waste generated from product processing should be classified by a competent environmental professional and disposed, processed, or recycled in accordance with federal, state and local regulations.
Handling and Storage	<p>Handling: Avoid breathing of and contact with fumes and dusts during processing. No specific requirements for solid formed steel product.</p> <p>Storage: Store away from incompatible materials (See Section 4). No other specific storage procedures are required for solid formed steel product.</p>

SECTION 8 – TOXICOLOGICAL INFORMATION
<p>Iron: Excessive exposure of eyes to airborne iron dust can cause conjunctivitis, choroiditis, and retinitis. Chronic inhalation of excessive concentrations of iron oxide fumes or dusts may result in development of a benign pneumoconiosis, called siderosis, which is observable via x-ray. No physical impairment of lung function has been associated with siderosis. Inhalation of excessive concentrations of iron oxide may enhance the risk of lung cancer development in workers exposed to pulmonary carcinogens. LD50 (oral, rat) – 30 gm/kg; LC50 – NIF.</p> <p>Chromium: The health hazards associated with exposure to chromium are dependent on its oxidation state. The metal form (chromium as it exists in this product) is of low toxicity. The hexavalent form and some trivalent forms are toxic. Adverse effects of the hexavalent form on the skin may include ulceration, dermatitis, and allergic skin reactions. Inhalation of hexavalent chromium compounds can result in ulceration and perforation of the mucous membranes of the nasal septum, irritation of the pharynx and larynx, asthmatic bronchitis, bronchospasms and edema. Respiratory symptoms may include coughing and wheezing, shortness of breath, and nasal itch. LD50 (oral – NIF; LC50 – NIF.</p> <p>Carcinogenicity – Chromium and most trivalent chromium compounds have been listed by NTP as having inadequate evidence for carcinogenicity in experimental animals. According to NTP, there is sufficient evidence for carcinogenicity in experimental animals for the following hexavalent chromium compounds: calcium chromate, chromium trioxide, lead chromate, strontium chromate, and zinc chromate. IARC has listed chromium metal and its trivalent compounds within Group 3 (the agent is not classifiable as to its carcinogenicity to humans). Chromium is not regulated as a carcinogen by OSHA (29 CFR 1910 Subpart Z). ACGIH has classified chromium metal and trivalent chromium compounds as A4, not classifiable as a human carcinogen. Water soluble hexavalent chromium compounds have been classified by ACGIH as A1, confirmed human carcinogen.</p> <p>Nickel: Nickel fumes are respiratory irritants and may cause pneumonitis. Exposure to nickel and its compounds may result in the development of dermatitis known as "nickel itch" in sensitized individuals. The first symptom is usually itching, which occurs up to 7 days before skin eruption occurs. The primary skin eruption is erythematous, or follicular, which may be followed by skin ulceration. Nickel</p>

SECTION 8 – TOXICOLOGICAL INFORMATION (Cont.)	
sensitivity, once acquired, appears to persist indefinitely. LC50 – NIF; LC50 (oral) – NIF.	
Carcinogenicity – Nickel and certain nickel compounds have been listed by NTP as being reasonably anticipated to be carcinogens. IARC has listed nickel compounds within group 1 (there is sufficient evidence for carcinogenicity in humans) and nickel within group 2B (agents which are possibly carcinogenic to humans). Nickel is not regulated as a carcinogen by OSHA (29 CFR 1910 Subpart Z). Based upon recent epidemiological data, ACGIH (1998) has designated elemental nickel as category A5, not a suspected human carcinogen.	
Molybdenum: Based on animal experiments, molybdenum and its compounds are highly toxic. Some evidence of liver dysfunction with hyperbilirubinemia has been reported in workmen chronically exposed in a Soviet Mo-Cu plant. In addition signs of gout have been found in factory workers and among inhabitants of Mo-rich areas of Armenia. The main features were joint pains in the knees, hands, feet, articular deformities, erythema, and edema of the joint areas. LD50 (oral) – NIF; LC50 – NIF.	
Silicon: Elemental silicon is an inert material, which appears to lack the property of causing fibrosis in lung tissue. However, slight pulmonary lesions have been reported in laboratory animals from intratracheal injections of silicon dust. Silicon dust has little adverse effect on lungs and does not appear to produce significant organic disease or toxic effects when exposures are below permissible limits. Silicon may cause chronic respiratory effects. Crystalline silica (silicon dioxide) is a potent respiratory hazard. However, the likelihood of crystalline silica generation during normal processing is very remote. LD50 (oral) – 3160 mg/kg rat; LC50 – NIF.	
Manganese: Chronic manganese poisoning may result from prolonged inhalation of manganese dust and fumes. The central nervous system is the chief site of damage from the disease, which may result in permanent disability. Symptoms include languor, sleepiness, weakness, emotional disturbances, spastic gait, recurring leg cramps, and paralysis. A high incidence of pneumonia and other upper respiratory infections has been found in workers exposed to dust or fume of manganese compounds. Manganese compounds are experimental equivocal tumorigenic agents. LD50 (oral, rat) – 30 gm/kg; LC50 – NIF; TClO – 2300 µg/m ³ (man).	
Tungsten: Tungsten has been shown to act by antagonizing the action of the essential trace element, Molybdenum. Tungsten metal powder administered to animals has been shown in several studies as not totally inert. One study found that guinea pigs treated orally or intravenously with tungsten suffered from anorexia, colic, incoordination of movement, trembling, dyspnea, and weight loss. Long industrial experience has indicated no pneumoconiosis to develop among workers exposed solely to tungsten or its insoluble compounds (at air concentrations of the order of 5 mg/m ³). In NIOSH's criteria document, two Russian studies were cited which indicated an incidence of 9-11% pulmonary fibrosis among employees exposed to tungsten without cobalt co-exposure. LD50 (intraperitoneal) – 5 g/kg rat; LC50 – NIF.	
Aluminum: Inhalation of finely divided aluminum and aluminum oxide powder has been reported as a cause of pulmonary fibrosis and lung damage. This effect, known as Shaver's Disease, is complicated by the presence in the inhaled air of silica and oxides of iron. May also be implicated in Alzheimer's disease. LD50 (oral) – NIF; LC50 – NIF.	
Columbium: Interferes with calcium as an activator of enzyme systems. LD50 (oral) – NIF; LC50 – NIF.	
Titanium: Elemental titanium and titanium dioxide is of a low order of toxicity. Laboratory animals (rats) exposed to titanium dioxide via inhalation have developed small localized areas of dark-colored dust deposits in the lungs. Excessive exposure in humans may result in slight changes in the lungs. LD50 (oral) – NIF; LC50- NIF.	
Copper: Industrial exposure to copper fumes, dusts, or mists may result in metal fume fever with atrophic changes in nasal mucous membranes. Chronic copper poisoning results in Wilson's Disease, characterized by a hepatic cirrhosis, brain damage, demyelination, renal disease, and copper deposition in the cornea. Copper fume (respirable) has appeared on the ACGIH Notice of Intended Changes (1996 & 1997). The intended ACGIH TLV for respirable copper fume is 0.05 mg/m ³ . LD50 (oral) – NIF; LC50 – NIF.	
Cobalt: Cobalt dust may cause an asthma-like disease with symptoms ranging from cough, shortness of breath, and dyspnea to decrease pulmonary function, nodular fibrosis, permanent disability, and death. Exposure to cobalt may cause weight loss, dermatitis, and respiratory hypersensitivity. LD50 (oral, rat) – 6171 mg/kg; LC50 – NIF.	
Carcinogenicity: IARC has listed cobalt and cobalt compounds within group 2B (agents which are possibly carcinogenic to humans). ACGIH has placed cobalt and inorganic compounds in category A3 (experimental animal carcinogen – the agent is carcinogenic in experimental animals at a relatively high dose, by route(s), histologic type(s), or by mechanism(s) that are not considered relevant to worker exposure. Cobalt has been classified by the Federal Republic of Germany to be carcinogenic to experimental animals.	

SECTION 9 – ECOLOGICAL INFORMATION	
N/A for solid steel product in its as shipped form. Articles produced from solid product are not an ecological hazard. NIF on specific products to establish its effect if released into the environment in finely divided form. It is believed that finely divided product, based on its components, will be hazardous to fish, animals, plants and the environment if released, the degree of which would depend on the particle size and quantity released. In addition, if particles are small enough, material may be ingested by wildlife, with possible toxic effects. The solid product is not expected to migrate easily into soil or ground water based upon its insoluble form, however, finely divided material can become mobile in water and contaminate soil and ground water. This material may persist in the environment for long periods, based upon its corrosion resistant, insoluble and non-biodegradable properties. In addition, heavy metals may contaminate the food chain and ultimately be consumed by humans. Some components will react with oxygen to form metallic oxides; the rate of oxidation depends upon prevailing conditions. Iron oxidizes most rapidly in moist air. Metallic particulate discharged to a POTW may pass-through of contaminate sewage sludge, may interfere with the treatment system process, and may be non-compliant with a POTW permit or other regulations.	

SECTION 10 – TRANSPORT INFORMATION	
Hazardous Materials Description/Proper Shipping Name:	N/A for solid formed product.
Hazard Class:	N/A for solid formed product.
Identification No.:	N/A for solid formed product.

SECTION 11 – REGULATORY INFORMATION	
SARA Title III Hazard Categorization:	Product (dust and fume) is categorized as an immediate (acute) health hazard and a delayed (chronic) health hazard as defined by 40 CFR 370.
SARA Title III Section 302 Extremely Hazardous Substances (EHSs):	No components are listed as extremely hazardous substances.
SARA Title III Section 313 Reportable Substances:	Nickel, Chromium, Cobalt, Aluminum (fume or dust), and Manganese are subject to reporting requirements. (Copper is less than the 1% de minimis level).
CERCLA Hazardous Substances:	*Nickel (threshold 100 lbs.), Chromium* (threshold 5000 lbs.), and Copper* (threshold 5000 lbs.). * Note: CERCLA reporting only if diameter of particles released is less than 100 micrometers.
Pennsylvania R-T-K List:	Listed components (greater than 0.1% by weight) – Aluminum (E), Manganese (E), Molybdenum, Nickel (E,S), Silicon, Chromium (E,S), Cobalt (E), Copper (E), and Tungsten. E – Environmental hazard, S – Special Hazardous Substance.
New Jersey R-T-K Environmental Hazardous Substance List:	Listed components – Aluminum (as dust and fume), Chromium, Cobalt, Copper, Manganese, and Nickel.
California Proposition 65:	Listed <u>possible</u> trace (must less than 0.1% by weight) elements known by the state to cause cancer – Arsenic (inorganic), Cadmium, Lead. Listed <u>possible</u> trace elements known by the state to cause reproductive toxicity – Lead. Listed components known by the state to cause cancer – Nickel, Cobalt (metal powder). Listed components known by the state to cause reproductive effects – None.

SECTION 12 – OTHER INFORMATION				
	Health	Flammability	Reactivity	PPE
NFPA RATING (for solid formed product):	1	0	0	
HMIS RATING (for solid formed product):	1	0	0	B

Abbreviations / Acronyms:			
ACGIH	American Conference of Governmental Industrial Hygienists	NIF	No Information Found
CAS	Chemical Abstracts Service	NIOSH	National Institute for Occupational Safety and Health
CFR	Code of Federal Regulations	NTP	National Toxicology Program
CPR	Cardiopulmonary Resuscitation	OSHA	Occupational Safety and Health Administration
CSA	Canadian Standards Association	PEL	Permissible Exposure Limit
EST	Eastern Standard Time	PNOR	Particulate Not Otherwise Regulated
HMIS	Hazardous Materials Identification System	PNOC	Particulate Not Otherwise Classified
IARC	International Agency for Research on Cancer	POTW	Publicly Owned Treatment Works
MSDS	Material Safety Data Sheet	PPE	Personal Protective Equipment
MSHA	Mine Safety and Health Administration	SCBA	Self-Contained Breathing Apparatus
NFPA	National Fire Protection Association	STEL	Short-Term Exposure Limit
N/A	Not Applicable	TLV	Threshold Limit Value
NIA	No Information Available.	TWA	Time-Weighted Average

Note: The percent composition in Section 1 reflects the range that is possible within this GROUP of products. These are not the technical specifications for a particular product. Also, specific grades may not include all of the hazardous ingredients in Section 1.

DISCLAIMER: The information contained herein is provided in good faith and is believed to be correct as of the date hereof. However, Precision Brand Products, Inc. makes no representation as to the comprehensiveness or accuracy of the information. It is expected that individuals receiving the information will exercise their independent judgment in determining its appropriateness for a particular period. Accordingly, Precision Brand Products, Inc. will not be responsible for damages of any kind resulting from the use of or reliance upon such information. NO REPRESENTATIONS, OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER NATURE ARE MADE HEREUNDER TO WHICH THE INFORMATION REFERS. The responsibility to provide a safe workplace remains with the user. The user should consider the health hazards and safety information contained herein as a guide and should take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment.